

NCAA #3 - 2016



Oil Pattern Distance 40 **Reverse Brush Drop** 36 Oil Per Board 50 ul **Forward Oil Total** 17.5 mL **Reverse Oil Total** 7.15 mL **Volume Oil Total** 24.65 mL **Tank Configuration Tank A Conditioner Tank B Conditioner A Only ICE FIRE**

1 2L 2R 2 18 74 0.0 2.5 2.5 3700 2 5L 5R 4 18 124 2.5 12.7 10.2 6200 3 9L 9R 4 18 92 12.7 22.9 10.2 4600 4 13L 13R 4 18 60 22.9 33.1 10.2 3000 5 2L 2R 0 22 0 33.1 40.0 6.9 0
3 9L 9R 4 18 92 12.7 22.9 10.2 4600 4 13L 13R 4 18 60 22.9 33.1 10.2 3000
4 13L 13R 4 18 60 22.9 33.1 10.2 3000
5 2L 2R 0 22 0 33.1 40.0 6.9 0

1 2L 2R 0 22 0 40.0 21.0 -19.0 0 2 13L 13R 1 18 15 21.0 18.5 -2.5 750 3 9L 9R 1 18 23 18.5 16.0 -2.5 1150 4 5L 5R 1 18 31 16.0 13.5 -2.5 1550 5 2L 2R 2 18 74 13.5 8.4 -5.1 3700 6 2L 2R 0 18 0 8.4 0.0 -8.4 0		START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
3 9L 9R 1 18 23 18.5 16.0 -2.5 1150 4 5L 5R 1 18 31 16.0 13.5 -2.5 1550 5 2L 2R 2 18 74 13.5 8.4 -5.1 3700	1	2L	2R	0	22	0	40.0	21.0	-19.0	0
4 5L 5R 1 18 31 16.0 13.5 -2.5 1550 5 2L 2R 2 18 74 13.5 8.4 -5.1 3700	2	13L	13R	1	18	15	21.0	18.5	-2.5	750
5 2L 2R 2 18 74 13.5 8.4 -5.1 3700	3	9L	9R	1	18	23	18.5	16.0	-2.5	1150
	4	5L	5R	1	18	31	16.0	13.5	-2.5	1550
6 2L 2R 0 18 0 8.4 0.0 -8.4 0	5	2L	2R	2	18	74	13.5	8.4	-5.1	3700
	6	2L	2R	0	18	0	8.4	0.0	-8.4	0

Cleaner Ratio Main Mix

Cleaner Ratio Back End Mix

NA

Reverse

Cleaner Ratio Back End Distance

NA

Combined

Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R	
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside	
Track Zone Ratio	2.71	1.46	1	1	1.46	2.71	



