



2025 U.S. Open Pattern 4



Oil Pattern Distance	41	Reverse Brush Drop	38	Oil Per Board	Multi ul
Forward Oil Total	10.36 mL	Reverse Oil Total	12.4 mL	Volume Oil Total	22.76 mL
Tank Configuration	B Only	Tank A Conditioner	FIRE	Tank B Conditioner	ICE

	START	STOP	LOADS	MICS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	5L	2	60	14	8	0.0	1.9	1.9	480
2	5R	2R	2	60	14	8	1.9	5.8	3.9	480
3	8L	8R	2	60	14	50	5.8	9.7	3.9	3000
4	2L	5L	2	60	14	8	9.7	13.6	3.9	480
5	5R	2R	2	60	14	8	13.6	17.5	3.9	480
6	8L	8R	2	40	14	50	17.5	21.4	3.9	2000
7	2L	5L	2	60	14	8	21.4	25.3	3.9	480
8	5R	2R	2	60	14	8	25.3	29.2	3.9	480
9	8L	8R	2	40	14	50	29.2	33.1	3.9	2000
10	2L	5L	1	60	14	4	33.1	35.0	1.9	240
11	5R	2R	1	60	14	4	35.0	36.9	1.9	240
12	2L	2R	0	60	14	0	36.9	41.0	4.1	0

	START	STOP	LOADS	MICS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	60	14	0	41.0	37.0	-4.0	0
2	2L	5L	1	60	14	4	37.0	35.1	-1.9	240
3	5R	2R	1	60	14	4	35.1	33.2	-1.9	240
4	8L	8R	2	40	14	50	33.2	29.3	-3.9	2000
5	2L	5L	2	60	14	8	29.3	25.4	-3.9	480
6	5R	2R	2	60	14	8	25.4	21.5	-3.9	480
7	8L	8R	2	40	14	50	21.5	17.6	-3.9	2000
8	2L	5L	2	60	14	8	17.6	13.7	-3.9	480
9	5R	2R	2	60	14	8	13.7	9.8	-3.9	480
10	8L	8R	4	60	10	100	9.8	4.2	-5.6	6000
11	2L	2R	0	60	10	0	4.2	0.0	-4.2	0

Cleaner Ratio Main Mix NA Forward
Cleaner Ratio Back End Mix NA Reverse
Cleaner Ratio Back End Distance NA Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Only compatible with ATLAS, ATLAS Walker or ATLAS Pro lane machines.

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	1.57	1	1	1	1	1.57

